AI-H8216

8ch 960H&8ch 1080P Touch HVR



Features

- 8ch 960H&8ch 1080P Touch HVR
- HDMI/VGA output
- Support 4ch simultaneous playback
- Support Android/IPhone remote view
- HDDx2，max 6TB

Overview

- 8ch 960H&8ch 1080P Touch HVR
- New Sensor Panel with finger touch control
- P2P function, one key to get auto ID (no need port forwarding)
- VGA/HDMI high definition output
- Support schedule snapshot, manual snapshot, alarm snapshot, FTP upload snapshot, playback and backup of the snapshot
- Support multiple protocols for PTZ control
- Electronic zoom in preview and playback
- Friendly playback and backup interface, easy to search, directly drag time bar, very easy for operation.
- Support smart phone remote view by Android, iPhone, Blackberry, Windows Mobile and Symbian
- Provide free DDNS
- Support NTP (Internet timing), DHCP (automatically get IP), Email (mail service), UPNP (Universal Plug and Play)
- Support 2 SATA HDD, max 6TB
- Support Multi-language: English, Brazilian, Russian, Portuguese, Spanish, Italian, Korean, French, German, etc.

Specifications

Model	**AI-H8216**
Video & audio input	
Analog video input	8PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
Audio input	8PCS RCA Port(Level : 2.0Vp-p, impedance : 1kΩ)
Network video input	8CH
Video & audio output	
HDMI output	800x600，1024x768，1280x1024，1440x900，720P，1080P
VGA output	800x600，1024x768，1280x1024，1440x900，720P，1080P
Audio output	1PCS RCA Port(line level , impedance : 1kΩ)
Video & audio code and decode parameters	
Record resolution	960H/D1/HD1CIF/720P/960P/1080P/3M
Playback resolution	D1 200/240FPS D1 100/120FPS+720P 100/120FPS
Motion detection	Motion Detection Depend on HVR
Synchronously playback channels	1/4/9CH
Record management	
Record & Snapshot mode	manual recording, regular recording, motion recording, alarm recording, events recording
Playback mode	regular playback,alarm playback,motion detection playback,events playback
Backup mode	regular backup, events backup, manual backup
Hard driver	
Mode	2*SATA
HDD capacity	each port support max 4TB HDD
External port	
Voice intercom	NO
Internet port	1PCS RJ45 10M / 100M adaptive Ethernet port
USB port	2*USB2.0
Alarm input	4
Alarm output	1
Network Management	
Network protocol	NTP、SMTP、PPPoE、DDNS、FTP、ARSP、WIFI、3G
Other	
Power supply	DC12V
Power consumption(without HDD)	≤18W
Work temperature	-10℃-- + 55℃
Work humidity	10%--90%
Case	1U
Size(W*L*H(cm))	335*255*50mm

Net weight(without HDD)	1.43kg
Gross weight(without HDD)	2.34kg
Color box size(L*W*H(cm))	39*30*11cm
Packing(pcs/carton)	5
Carton size (L*W*H(cm))	57*40.7*32.6cm
Gross weight(kg)	12.59kg

Back Panel Picture

